

NEW

racer




S1P

EN ISO 20345: 2011 SRC

PRODUCT CHARACTERISTICS



Non-magnetic



Breathable

THE + PARADE TECHNOLOGY EXTRAS



DRS SYSTEM 2

New DRS version



VPS SYSTEM

Supports the arch of the foot



Be flex 2.0

Extra-flexible sole



SHIELD ONE

Abrasion resistance level 4



LIGHT,
COMFORTABLE
TRAINER

7824 BLACK | SIZE: 35 TO 48

COMPOSITION

Upper	Canvas + PU
Lining	3D mesh
Toe	Composite
Insole	Mesh over PU foam. Removable.
Anti-puncture sole	Non-metallic
Sole	Dual-density polyurethane
Weight size 42*	580 g * Weight per shoe

SAFETY TABLE

	Safety toe (resistant to 200 joules)
	Anti-puncture sole
	Non-slip** sole
	Shock-absorbent
	Anti-static
	Hydrocarbon-resistant

**

Size coefficient 42	Flat		Heel	
	Standard	Parade	Standard	Parade
SRA Anti-slip ceramic / Nals (soap solution)	0,32	0,49	0,28	0,54
SRB Anti-slip steel / Glycerine (oil)	0,18	0,18	0,13	0,15